60137-042 001-3035-U

AMENDMENTS TO THE CLAIMS:

Please amend the claims as follows. This listing of claims will replace all prior listings.

- 1. (CURRENTLY AMENDED) A drum release assembly for a drain cleaning machine comprising:
 - a sleeve defining an axis of rotation;
 - a plate having an inner opening defined about said axis of rotation;
 - a latch movably mounted relative to said inner opening and substantially perpendicular to said axis of rotation; and
 - a biasing member to bias said latch away from said axis of rotation.
- 2. (ORIGINAL) The drum release assembly as recited in claim 1, wherein said plate includes an annular disk.
- 3. (ORIGINAL) The drum release assembly as recited in claim 2, wherein said disk is fixedly mounted to a rotary drum.
- 4. (ORIGINAL) The drum release assembly as recited in claim 1, wherein said inner opening of said plate is spaced away from a rotary drum.
- 5. (ORIGINAL) The drum release assembly as recited in claim 1, further comprising a latch sleeve, said latch telescopically mounted within said latch sleeve to extend past said inner opening.
- 6. (ORIGINAL) The drum release assembly as recited in claim 5, wherein said latch sleeve extends in a perpendicular arrangement from said sleeve.
- 7. (ORIGINAL) The drum release assembly as recited in claim 5, wherein said latch sleeve includes a first and second latch sleeve mounted to said sleeve in a T-shaped arrangement.

60137-042 001-3035-U

- 8. (CURRENTLY AMENDED) The drum release assembly as recited in claim 1, wherein said latch includes a we ge-shaped face engagable engageable with said inner opening.
- 9. (CURRENTLY MENDED) The drum release assembly as recited in claim 1, further comprising an actuator handle engageable with said latch.
- 10. (CURRENTLY MENDED) The drum release assembly as recited in claim 9, wherein said actuating actuator handle includes comprises a cam surface engageable with a pin extending from said latch.
 - 11. (CURRENTLY MENDED) A release assembly for a drain cleaning machine comprising:
 - a sleeve to rotatally receive a rotary drum shaft defining an axis of rotation; an annular disk having an inner opening defined about said axis of rotation;
 - a latch sleeve extending perpendicular from said sleeve in a perpendicular arrangement;
 - a latch telescopically mounted within said latch sleeve; and
 - a biasing member to bias said latch away from said axis of rotation to retain said disk with said latch.
- 12. (CURRENTLY AMENDED) The drum release assembly as recited in claim 11, wherein said inner opening of said annular disk is spaced away from a said rotary drum.
- 13. (CURRENTLY MENDED) The drum release assembly as recited in claim 11, wherein said latch extends past said inner opening.
- (ORIGINAL) The release assembly as recited in claim 11, further comprising an actuator hardle having a cam surface engageable with a pin extending from said latch.

60137-042
001-3035-U

15. (CURRENTLY MENDED) The release assembly as recited in claim 14, wherein said pin extends through a slot defined by a said latch sleeve.

16. (ORIGINAL) A frain cleaning machine comprising:

a support frame;

a removable rotary drum;

a rotary drum shaft extending from said rotary drum, said rotary drum shaft defining an axis of rotation;

a drive assembly o rotate said rotary drum about said axis of rotation;

a sleeve mounted to said frame to rotatably receive said rotary drum shaft defining an axis of rotation;

an annular disk having an inner opening defined about said axis of rotation, said annular disk mounted to said removable rotary drum, said inner opening spaced away from a face of said removable rotary drum;

a latch sleeve extending perpendicular from said sleeve in a perpendicular arrangement;

a latch telescopically mounted within said latch sleeve; and

a biasing member to bias said latch away from said axis of rotation to retain said annular disk with said latch.

17. (CURRENTLY MENDED) The drain cleaning machine as recited in claim 16, wherein said latch includes a wedge-shaped face engageable engageable with said inner opening.

18. (ORIGINAL) The drain cleaning machine as recited in claim 16, further comprising an actuator handle aving a cam surface engageable with a pin extending from said latch.

19. (CANCELED)

60137-042 001-3035-U

20. (ORIGINAL) The drain cleaning machine as recited in claim 16, wherein said sleeve contains a bearing to receive said rotary drum shaft.